

TS4-D



Diodes

TS4-D is one of six functional covers that pairs with an integrated modular junction box base.

Features

- Similar to a standard junction box
- Standardization on TS4 baseplate
- Field replaceable and upgradeable
- Heat dissipation away from the module

Smart Ready

- All TS4 integrated modules share a common base
- Upgrade your PV module with smart features at any time by replacing the TS4 cover

Keep it cool

- Better heat dissipation behind the module reduces hotspots
- TS4-D keeps your solar cells 5°C cooler than a standard junction box

Replaceable

- Bypass diodes are contained in the cover, making them field serviceable with minimal downtime
- TS4 covers can be changed on the roof using basic tools





Meet any projects' needs with the TS4 covers

Tigo has expanded its smart module platform to provide six levels of customization. TS4 increases your freedom of choice by allowing you to select the right features for each project and budget.

ELECTRICAL RATINGS

INPUT	
Rated DC Input Power	-
Maximum Input Voltage @ Lowest Temperature	-
Maximum Short Circuit Current (I_{SC})	12.5A
Maximum V_{OC} @ STC	-
Minimum V_{MP} @ STC	-
OUTPUT	
Output Power Range	0 - P_{MAX}
Output Voltage Range	0 - V_{OC}
Rapid Shutdown Capability (NEC 2014 690.12)	Need additional RS device
Impedance Matching Capability	No
Output Voltage Limit	No
Maximum System Voltage	1500V
Maximum Series Fuse Rating	15A



DIODES
TS4-D

For sales info:

sales@tigoenergy.com or 1.408.402.0802 ext. 1

For product info:

Visit www.tigoenergy.com/products

For technical info:

<http://support.tigoenergy.com>

For additional info and product selection assistance, use Tigo's online design tool at www.tigoenergy.com/design

